Local catalogue draft · Preview only. Product data and documents are not released. Open catalogue review

Draft without a blocking review case

This view is not engineering approval. Open and withheld information remains unresolved.

▶ 6 open or withheld review cases



Reference image: 250 mm. See the technical data for the actual product length. 1 / 1

PROFILES

080 Support Profile - 1000mm

Article number
X-M-PR-1000

REQUEST A QUOTE

The support-arm profile forms the straight connecting element in the X-M support-arm system. It defines the distance between the connection and joint modules and is combined with components from this profile series. This version has a length of 1,000 mm. The layout of the support-arm assembly can therefore be matched to the position of the operator enclosure and the intended workstation.

Weight
4,000 g

Colour
RAL 7035

Package Dimensions
65 × 90 × 1010 mm

HS Code
7606.99.90.19

Warranty
5 years

Technical data

Specifications for planning, selection and use at a glance.

Material & finish

RAL colours	RAL 7035

Application & function

Operating Weight	4,000 g
Primary Use Case	Machine Building / Automation / HMI operator stations
Operating Temperature	–40°C to +70°C
Protection Rating	IP65 (DIN EN 60529)
Rated Voltage	Mechanical (not subject to electrical certification)

Safety & compliance

Earthing	Yes, integrated solution
RoHS Compliance	RoHS EU Directive 2011/65/EU
REACH Compliance	REACH Regulation 1907/2006/EC
Certification	IEC 60529; (EG) No. 765/2008; (EU) 2023/956

Further information

Length	1,000 mm
Load at 1,000 mm arm length	80 kg
Custom lengths available	Yes

Ordering & delivery information

Package dimensions

65 × 90 × 1010 mm

HS Code

7606.99.90.19

Warranty

5 years

Version & enquiry

Use the item number and version to prepare your enquiry.

Search SKU or name...

1 of 1 mm in

SKU ↑	LENGTH (MM) ↑↓	WEIGHT (G) ↑↓	Choose a version
SKU: X-M-PR-1000	1000	4000	Select