


Product Overview / Produktueberblick

Product photos / Produktfotos



Technical drawing preview / Technische Zeichnung Vorschau



Triple Pedal Foot Switch

Dreifachpedal-Fussschalter

-40 C to +80 C

20M cycles

IP20/IP40

Series / Reihe

XX-PDL3xxx

Item codes /
Artikelcodes

XX-PDL3110 (Red),
XX-PDL3120 (Yellow),
XX-PDL3140 (Black)

Dimensions (W x D x H)
/ Masse

407 x 150 x 250 mm

Material / Material

High-grade Aluminium 6000
protective shroud

Use case /
Einsatzbereich

Machine building,
automation, operator
stations

Color options /
Farboptionen

Red, Yellow, Black

Technical Specifications / Technische Spezifikationen

Series / Reihe	XX-PDL3xxx
Product class / Produktklasse	Triple Pedal Foot Switch / Dreifachpedal-Fussschalter
Item codes / Artikelcodes	XX-PDL3110 (Red), XX-PDL3120 (Yellow), XX-PDL3140 (Black)
Dimensions (W x D x H) / Masse	407 x 150 x 250 mm
Material / Material	High-grade Aluminium 6000 protective shroud
Operating temperature / Betriebstemperatur	-40 C to +80 C
Mechanical endurance / Mechanische Lebensdauer	20 million operating cycles
Max actuation frequency / Max Schaltfrequenz	3600 operating cycles per hour
Thermal current (Ith) / Thermischer Strom	10 A
Rated impulse withstand voltage (Uimp)	6 kV
Protection (contact block) / Schutzart	IP20 (terminals), IP40 (contacts)
Safety application / Sicherheitsanwendung	Use positive-opening NC contacts per EN ISO 14119
Standards / Normen	EN 60947-1, EN 60947-5-1, EN ISO 14119, EN ISO 12100, EN 60529, EN IEC 63000
Certifications / Zertifizierungen	IMQ CA02.06217, UL/cULus E131787, CCC 2024010305656752, EAC RU D-IT.PA07.B.37848/24, EU DoC, UKCA DoC

Application Note / Anwendungshinweis

Values are based on VF B series technical/certification documents and apply at series level.

Werte basieren auf den VF-B-Seriendokumenten und gelten auf Serienebene.