


XINDUX XX-TA050.xxx Support Arm Profile - Technical Datasheet

Technischer Querschnitt / Technical Cross Section, Profilgrößen / Profile Sizes, Lasten / Loads.

Technischer Querschnitt / Technical Cross Section	Merkmal / Feature	Wert / Value
	Aussenmass / Outer Dimension	70.00 x 48.50 mm
	Innenmass / Inner Dimension	64.50 x 43.00 mm
	Bohrmass / Drill Pattern	54.00 x 31.00 mm
	Lochbild / Hole Pattern	Ø5.40 mm x4
	Bohrungen / Holes	4
	Winkeleinstellung / Angle Adjustment	Nein / No
	Material / Material	Aluminium 6060
	HS Code	7606.99.90.19

Profilgrößen / Profile Sizes (Katalog / Catalogue)				
XINDUX Code	Laenge / Length (mm)	Gewicht / Weight (g)	RAL	Paketmass / Package (mm)
XX-TA050.025	250	500	7035	50 x 75 x 260
XX-TA050.050	500	1000	7035	50 x 75 x 510
XX-TA050.075	750	1500	7035	50 x 75 x 760
XX-TA050.100	1000	2000	7035	50 x 75 x 1010
XX-TA050.125	1250	2500	7035	50 x 75 x 1260
XX-TA050.150	1500	3000	7035	50 x 75 x 1510
XX-TA050.175	1750	3500	7035	50 x 75 x 1760
XX-TA050.200	2000	4000	7035	50 x 75 x 2010

Lastdiagramm / Load Diagram



Statische Kraft in N / Static force in N, aus Katalogdiagramm abgeleitet / derived from catalogue diagram.

Kurve / Curve	Punkt 1 / Point 1	Punkt 2 / Point 2	Punkt 3 / Point 3
Kurve 1 (ca.)	0 mm / 1200 N	1000 mm / 570 N	2000 mm / 0 N
Kurve 2 (ca.)	0 mm / 650 N	1000 mm / 250 N	1500 mm / 0 N

Katalog 2024 / Catalogue 2024: Lastdiagramm S.9 / Load Diagram p.9, Profiltabelle S.16 / Profile Table p.16